

Rotary hammer TE 7-C



Applications

- Drilling and hammer drilling in concrete and masonry
- Corrective chiseling and small channel openings in concrete
- Occasional drilling in wood and steel with optional quick-release chuck
- Drilling in concrete in clean areas using the integrated dust removal system (DRS-M)
- Cutting socket recesses in masonry

Advantages

- Ergonomically designed D-grip for comfortable use over long periods
- Robustly built and superbly engineered for maximum reliability and long life
- Interchangeable "TE-C Click" chuck system for versatility and ease of use
- Virtually dustless drilling with the DRS-M dust removal system
- High drilling performance
- Electronic switch for precise hole-starting

Technical data

Working mode	Hammer drilling, Drilling only, Chiselling, Chisel setting
Drilling diameter range for hammer drill bits	4 - 28 mm
Single impact energy	2.6 J
Triaxial vibration value for hammer drilling into concrete (ah,HD)¹⁾	17 m/s ²
A-weighted emission sound pressure level²⁾	89 dB (A)
Dust removal module	TE DRS-M (optional)
Full hammering frequency	4020 impacts/minute
Dimensions (LxWxH)	343 x 86 x 215 mm
Weight according to EPTA Procedure 01/2003	3.4 kg
Approvals	CE, UL

¹⁾ according to EN 60745-2-6

²⁾ according to EN 60745



Ordering designation	Package contents	Sales pack quantity	Item number
TE7C	1x Rotary hammer TE 7-C 230V GB, 1x Case	1 pc	228056

Please visit our website for the latest item numbers and related products.