

Breaker TE 700-AVR





Applications

- Heavy wall demolition on masonry and brick
- Large-scale plaster removal
- Tile removal on walls and floors
- Window and door openings
- Bushing applications for roughening or smoothing surfaces
- Correctional work in new construction

Advantages

- Highest impact energy in the 7kg class (11,5J)
- Brushless SR drive outstanding lifetime
- Sub-chassis AVR for greater working comfort (6.5m/s²)
- Inline shape well balanced, great handling
- Power reduction more flexibility

HILLIE	6 ^{Months}
LIFETIME	NO COSTS
Lifetime	Lifetime
REPAIR COST LIMIT	MANUFACTURER'S WARRANTY





Technical data		
Rated input power	1300 W	
Single impact energy	11.5 J	
Full hammering frequency	2760 impacts/minute	
Max. chiselling performance	1200 cm³/min	
Reduced impact energy	Yes	
A-weighted emission sound pressure level ¹⁾	86 dB (A)	
Active Vibration Reduction	Yes	
Service indicator	Yes	
Triaxial vibration for chiselling in concrete ²⁾	6.5 m/s ²	
Weight according to EPTA Procedure 01/2003	7.9 kg	

¹⁾ according to EN 60745

²⁾ according to EN 60745-2-6



Ordering designation	Package contents	Sales pack quantity	Item number
TE 700-AVR	1x Breaker TE 700-AVR 230V GB, 1x Case	1 pc	3484303

Please visit our website for the latest item numbers and related products.