

**Safety anchor (stainless steel) HSC-AR**



**Base materials**

- Concrete (cracked)
- Concrete (uncracked)

**Applications**

- Safety-relevant, medium-duty fastenings in cracked or uncracked concrete and corrosive environments, especially where shallow embedment and/or small edge distance or close spacing is required
- Examples: stair hand rails, balcony safety railings, sprinkler pipes, air ducts, seating, facade substructures, car park barriers, etc.

**Advantages**

- Shallow embedment depth for thin concrete slabs or where permissible drilling depth is limited
- Combines high working loads with small edge distances and close spacing thanks to very low expansion forces
- Self-undercutting facilitates fast and reliable installation - no separate undercutting tool or handling needed


**Technical data**

|                                       |   |
|---------------------------------------|---|
| <b>Material composition</b>           | Steel, A4 (SS316)   |
| <b>Head configuration</b>             | Externally threaded   |
| <b>PROFIS</b>                         | Yes   |
| <b>Additional product information</b> | Meets approval requirements when installed using the specified stop drill bit, setting tool and rotary hammer |

**Approvals**

|           |  |
|-----------|--|
| BZS/shock | BZS for HSC                                |
| ETA       | ETA-02/0027 for HSC (ETAG 001-3, Option 1) |

Approvals and test reports may apply to selected products only. Please refer to the documents for details.



These are abbreviated instructions which may vary by application. Always review/follow the instructions accompanying the product or refer to [www.hilti.com/techlib](http://www.hilti.com/techlib).

**Anchor Systems**

| Ordering designation | Anchor size | Max. fixture thickness at standard | Base plate clearance hole | Drilling depth | Required tightening torque | Wrench size | Sales pack quantity | Item number         |
|----------------------|-------------|------------------------------------|---------------------------|----------------|----------------------------|-------------|---------------------|---------------------|
| HSC-AR M8x40/15      | M8          | 15 mm                              | 9 mm                      | 46 mm          | 10 Nm                      | 13 mm       | 25 pc               | 31148 <sup>1)</sup> |
| HSC-AR M8x50/15      | M8          | 15 mm                              | 9 mm                      | 56 mm          | 10 Nm                      | 13 mm       | 25 pc               | 31150 <sup>1)</sup> |
| HSC-AR M10x40/20     | M10         | 20 mm                              | 12 mm                     | 47 mm          | 20 Nm                      | 17 mm       | 25 pc               | 31149 <sup>1)</sup> |
| HSC-AR M12x60/20     | M12         | 20 mm                              | 14 mm                     | 68 mm          | 30 Nm                      | 19 mm       | 20 pc               | 15506               |

<sup>1)</sup> This is a non-stock item. For detailed lead time information please contact your Hilti representative.

Please visit our website for the latest item numbers and related products.