SAFETY DATA SHEET



Tribol GR 400-2 PD

Section 1. Identification

GHS product identifier Tribol GR 400-2 PD **Product code** 468725-US17 SDS no. 468725

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/ Grease for industrial applications.

For specific application advice see appropriate Technical Data Sheet or consult our mixture

company representative.

Manufacturer

Supplier PT. Castrol Indonesia

Perkantoran Hijau Arkadia, Tower G Lt.3

JI. TB Simatupang Kav. 88 Jakarta 12520 - Indonesia

Tel: (62-21) 78838000, Fax: (62-21) 78549165

Lavanan Konsumen:

Castrol We Care 0807 1 932273 (Pulsa lokal)

EMERGENCY TELEPHONE

NUMBER

Carechem: 00780 3011 0293 (toll-free, access from Indonesia only)

Section 2. Hazards identification

GHS Classification LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3

GHS label elements, including precautionary statements

Signal word No signal word.

Hazard statements H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention P273 - Avoid release to the environment.

Response Not applicable. **Storage** Not applicable.

Disposal P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Other hazards which do not

result in classification

Defatting to the skin.

Note: High Pressure Applications

Injections through the skin resulting from contact with the product at high pressure

constitute a major medical emergency.

See 'Notes to physician' under First-Aid Measures, Section 4 of this Safety Data

Sheet.

Mixture

Section 3. Composition/information on ingredients

Substance/mixture

Highly refined mineral oil and additives. Thickening agent.

Ingredient name	%	CAS number
Residual oils (petroleum), hydrotreated	≥50 - ≤75	64742-57-0
Distillates (petroleum), solvent-dewaxed heavy paraffinic	≥25 - ≤50	64742-65-0
Distillates (petroleum), hydrotreated heavy paraffinic	≥10 - ≤25	64742-54-7
2,6-di-tert-butyl-4-nonylphenol	≤0.3	4306-88-1

Product name Tribol GR 400-2 PD Product code 468725-US17 Page: 1/9 Version 1.01 Date of issue 18/01/2023. Language ENGLISH Format GHS - Indonesia (ENGLISH)

Build 5.2.6 (GHS - Indonesia)

Section 3. Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. Never give

anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if adverse

health effects persist or are severe.

Skin contact Wash skin thoroughly with soap and water or use recognised skin cleanser.

Remove contaminated clothing and shoes. Wash clothing before reuse. Clean

shoes thoroughly before reuse. Get medical attention if symptoms occur.

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for

and remove any contact lenses. Get medical attention.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Specific treatments No specific treatment.

Notes to physician Treatment should in general be symptomatic and directed to relieving any effects.

Note: High Pressure Applications

Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discoloured and extremely painful with

extensive subcutaneous necrosis.

Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimise tissue loss and prevent or limit permanent damage. Note that high pressure may force the

product considerable distances along tissue planes.

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing

media

In case of fire, use water fog, alcohol resistant foam, dry chemical or carbon dioxide

extinguisher or spray.

Unsuitable extinguishing media

Do not use water jet.

Specific hazards arising from the chemical

Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. This material is harmful to

aquatic life with long lasting effects.

Hazardous thermal decomposition products Combustion products may include the following:

metal oxide/oxides

carbon oxides (CO, CO2) (carbon monoxide, carbon dioxide)

Special protective actions

for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

Special protective equipment for fire-fighters Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Product name Tribol GR 400-2 PD Product code 468725-US17 Page: 2/9 Date of issue 18/01/2023. Language ENGLISH Format GHS - Indonesia Version 1.01 (ENGLISH) Build 5.2.6 (GHS - Indonesia)

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and material for containment and cleaning up

Small spill

Move containers from spill area. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. If emergency personnel are unavailable, contain spilt material. Suction or scoop the spill into appropriate disposal or recycling vessels, then cover spill area with oil absorbent. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Avoid contact of spilt material and runoff with soil and surface waterways.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Prolonged exposure to elevated temperature

Section 8. Exposure controls/personal protection

Control parameters

Not suitable

Occupational exposure limits

Product name Tribol GR 400-2 PDProduct code468725-US17Page: 3/9Version 1.01Date of issue 18/01/2023.Format GHS - IndonesiaLanguage ENGLISHBuild 5.2.6(GHS - Indonesia)(ENGLISH)

Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits
Residual oils (petroleum), hydrotreated	Minister of Labor of the Republic of Indonesia (Indonesia). [Mineral oils] TWA: 5 mg/m³ 8 hours. Issued/Revised: 4/2018 Form: Mist STEL: 10 mg/m³ 15 minutes. Issued/ Revised: 4/2018 Form: Mist
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Minister of Labor of the Republic of Indonesia (Indonesia). [Mineral oils] TWA: 5 mg/m³ 8 hours. Issued/Revised: 4/2018 Form: Mist STEL: 10 mg/m³ 15 minutes. Issued/ Revised: 4/2018 Form: Mist
Distillates (petroleum), hydrotreated heavy paraffinic	Minister of Labor of the Republic of Indonesia (Indonesia). [Mineral oils] TWA: 5 mg/m³ 8 hours. Issued/Revised: 4/2018 Form: Mist STEL: 10 mg/m³ 15 minutes. Issued/ Revised: 4/2018 Form: Mist

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures

Appropriate engineering controls

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection Skin protection

Hand protection

Safety glasses with side shields.

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

 Product name Tribol GR 400-2 PD
 Product code 468725-US17
 Page: 4/9

 Version 1.01
 Date of issue 18/01/2023.
 Format GHS - Indonesia
 Language ENGLISH

 Build 5.2.6
 (GHS - Indonesia)
 (ENGLISH)

Section 8. Exposure controls/personal protection

Skin protection Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist

before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

In case of insufficient ventilation, wear suitable respiratory equipment. Respiratory protection

For protection against metal working fluids, respiratory protection that is classified as

"resistant to oil" (class R) or oil proof (class P) should be selected where appropriate. Depending on the level of airborne contaminants, an air-purifying, half-mask respirator (with HEPA filter) including disposable (P- or R-series) (for oil mists less than 50mg/m3), or any powered, air-purifying respirator equipped with hood or

helmet and HEPA filter (for oil mists less than 125 mg/m3).

Where organic vapours are a potential hazard during metalworking operations, a

combination particulate and organic vapour filter may be necessary.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state Grease Colour Brown. **Odour** Not available. Not available. **Odour threshold** pH Not applicable. **Melting point** Not available.

Boiling point, initial boiling point, and boiling range

Not available.

Flash point

Open cup: 268°C (514.4°F) [Estimated. Based on Lubricants - Base Oils]

Evaporation rate

Not available.

Flammability

Not applicable. Based on - Physical state

Lower and upper explosion limit/flammability limit

Not applicable.

Vapour pressure

Not available.

	Vapour Pressure at 20°C			Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method

Relative vapour density

Not applicable.

Density

<1000 kg/m3 (<1 g/cm3) at 20°C

Relative density

Not available.

Solubility(ies)

Media	Result
water	Not soluble

Partition coefficient: n-

octanol/water

Not applicable.

Auto-ignition temperature Decomposition temperature Not applicable. Not available.

Viscosity

Not available.

Particle characteristics

Product name Tribol GR 400-2 PD Product code 468725-US17 Page: 5/9 Version 1.01 Date of issue 18/01/2023. Language ENGLISH Format GHS - Indonesia

Build 5.2.6 (GHS - Indonesia) (ENGLISH)

Section 9. Physical and chemical properties

Median particle size : Not available.

Section 10. Stability and reactivity

Reactivity No specific test data available for this product. Refer to Conditions to avoid and

Incompatible materials for additional information.

Chemical stability The product is stable.

Possibility of hazardous

Under normal conditions of storage and use, hazardous reactions will not occur. reactions Under normal conditions of storage and use, hazardous polymerisation will not occur.

Conditions to avoid Avoid all possible sources of ignition (spark or flame).

Incompatible materials Reactive or incompatible with the following materials: oxidising materials.

Hazardous decomposition Under normal conditions of storage and use, hazardous decomposition products

should not be produced. products

Section 11. Toxicological information

Information on toxicological effects

Information on likely routes Routes of entry anticipated: Dermal, Inhalation, Eyes.

of exposure

Potential acute health effects

Eye contact No known significant effects or critical hazards. Inhalation No known significant effects or critical hazards.

Skin contact Defatting to the skin. May cause skin dryness and irritation.

Ingestion No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact No specific data. Inhalation No specific data.

Skin contact Adverse symptoms may include the following:

> irritation dryness cracking

Ingestion No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs. Inhalation

Inhalation of oil mist or vapours at elevated temperatures may cause respiratory

irritation.

Skin contact Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/

or dermatitis.

Ingestion Ingestion of large quantities may cause nausea and diarrhoea.

Short term exposure

Potential immediate Not available.

effects

Not available. Potential delayed effects

Long term exposure

Potential immediate Not available.

effects

Potential delayed effects Not available.

General No known significant effects or critical hazards. Carcinogenicity No known significant effects or critical hazards. Mutagenicity No known significant effects or critical hazards. **Teratogenicity** No known significant effects or critical hazards. **Developmental effects** No known significant effects or critical hazards. **Fertility effects** No known significant effects or critical hazards.

Numerical measures of toxicity

Product name Tribol GR 400-2 PD 468725-US17 Product code Page: 6/9 Date of issue 18/01/2023. Language ENGLISH Version 1.01 Format GHS - Indonesia (ENGLISH) Build 5.2.6 (GHS - Indonesia)

Section 11. Toxicological information

Acute toxicity estimates

Not available.

Section 12. Ecological information

Environmental effects

This material is harmful to aquatic life with long lasting effects.

Persistence/degradability

Not expected to be rapidly degradable.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (K_{oc})

Not available.

Mobility Grease. insoluble in water.

Other adverse effects No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	IMDG	IATA
UN number	Not regulated.	Not regulated.
UN proper shipping name	-	-
Transport hazard class(es)	-	-
Packing group	-	-
Environmental hazards	No.	No.
Additional information	-	-

Special precautions for user Not available.

Product nameTribol GR 400-2 PDProduct code468725-US17Page: 7/9Version 1.01Date of issue 18/01/2023.Format GHS - IndonesiaLanguage ENGLISHBuild 5.2.6(GHS - Indonesia)(ENGLISH)

Section 15. Regulatory information

Law No. 74/2001 - Banned

None of the components are listed.

Law No. 74/2001 - Restricted

None of the components are listed.

Ministry of Health - Law No. 472/Menkes/Per/V/1996

Carcinogen

None of the components are listed.

Corrosive

None of the components are listed.

None of the components are listed.

Mutagen

None of the components are listed.

Oxidiser

None of the components are listed.

Poison

None of the components are listed.

Teratogen

None of the components are listed.

International lists

National inventory

Australia inventory (AIIC) All components are listed or exempted.

Canada inventory status At least one component is not listed in DSL but all such components are listed in

NDSL.

China inventory (IECSC)

REACH Status

All components are listed or exempted.

The company, as identified in Section 1, sells this product in the EU in compliance with the

current requirements of REACH.

Japan inventory (CSCL) **Philippines inventory**

(PICCS)

At least one component is not listed. At least one component is not listed.

Korea inventory (KECI)

Taiwan Chemical

Substances Inventory

At least one component is not listed.

All components are listed or exempted.

United States inventory

(TSCA 8b)

All components are active or exempted.

Section 16. Other information

History

18 January 2023 Date of issue/Date of

revision

11 October 2022 Date of previous issue Prepared by

Key to abbreviations

Product Stewardship ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

Regulation [Regulation (EC) No. 1907/2006]

Product name Tribol GR 400-2 PD Product code 468725-US17 Page: 8/9 Date of issue 18/01/2023. Language ENGLISH Version 1.01 Format GHS - Indonesia

> Build 5.2.6 (GHS - Indonesia) (ENGLISH)

Section 16. Other information

UN = United Nations

Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

▼ Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name Tribol GR 400-2 PDProduct code468725-US17Page: 9/9Version 1.01Date of issue 18/01/2023.Format GHS - IndonesiaLanguage ENGLISHBuild 5.2.6(GHS - Indonesia)(ENGLISH)